

**100 % ready to use,  
0 % energy consumption**

**C.A 6501,**  
insulation measurements  
up to 200 M $\Omega$   
(test at 500 V)

**MEGOHMMETERS**



**C.A 6503,**  
insulation measurements  
up to 5,000 M $\Omega$   
(test at 250 V / 500 V / 1,000 V)

- Simple, immediate implementation
- Rigorously constant test voltage
- Automatic switching between calibres
- Automatic discharge after measurement
- Measurements in compliance with standards such as NF C 15-100, VDE 0100, etc.

Lightweight and compact, the **C.A 6501** and **C.A 6503** insulation testers are handheld instruments which are totally independent because they are powered by a magneto. Particularly versatile, they are ideal for on-site, industrial and domestic environments... They can be used for a large number of applications, such as ensuring that electrical installations comply with the applicable standards or carrying out preventive maintenance on cables and motors. A LED indicates when the measurement conditions are correct.

The **C.A 6503** has a protective terminal designed to limit the influence of leakage currents on the measurements.

Technical Specifications		
	C.A 6501	C.A 6503
<b>INSULATION</b>		
Test voltages (DC) Ranges	500 V	250 V / 500 V / 1 000 V
	up to 200 M $\Omega$	250 V: 1 to 11 M $\Omega$ - 11 to 500 M $\Omega$ 500 V: 1 to 11 M $\Omega$ - 11 to 500 M $\Omega$ 1,000 V: 10 to 110 M $\Omega$ - 110 to 5,000 M $\Omega$
Short-circuit current	5 mA (max)	5 mA (max)
Accuracy	2.5 % of scale length	2 % of scale length
Automatic discharge	5 s/ $\mu$ F	8 s/ $\mu$ F
Charge time	0.5 s/ $\mu$ F	250 V: 0.2 s/ $\mu$ F 500 V: 0.5 s/ $\mu$ F 1,000 V: 0.5 s/ $\mu$ F
<b>RESISTANCE</b>		
Ranges	0 to 45 k $\Omega$ / 45 to 500 k $\Omega$	
Measurement current	1 mA <sub>DC</sub>	
Accuracy	2.5 % of scale length	
Automatic discharge	5 s/ $\mu$ F	
<b>CONTINUITY</b>		
Ranges	0 to 9 $\Omega$ / 9 $\Omega$ to 100 $\Omega$	
Measurement current	5 mA <sub>DC</sub>	
Accuracy	2 % of scale length	
Protection	F-type 0.2 A 700 V HRC fuse (6.3 x 32)	
<b>VOLTAGE</b>		
Ranges	0 ... 600 V <sub>AC</sub>	
Frequency	45 to 450 Hz	
Input impedance	100 k $\Omega$	
Accuracy	3 % of the scale	
General Specifications		
Scale	Direct reading on a 3" B&W screen	
LED	1. Ensures that the measurement conditions are correct 2. Indicates automatic calibre switching	
Dimensions	120 x 120 x 130 mm	
Weight	1.06 kg	
Power supply	Magneto allowing a stable test voltage	
Electrical safety	IEC 61010 CAT II 600 V / CAT III 300 V	

#### State at delivery:

- **CA6501:** delivered with 1 user's guide, 1 carrying bag, 2 x 1.5 m PVC elbowed/straight leads (black/red), 2 crocodile clips (black/red), 1 black test probe.

**P01132503**

- **CA6503:** delivered with 1 user's guide, 1 carrying bag, 3 x 1.5 m black PVC elbowed/straight leads (black/red/blue), 3 crocodile clips (black/red/blue), 1 black test probe.

**P01132504**



**FRANCE**  
**Chauvin Arnoux**  
 190, rue Championnet  
 75876 PARIS Cedex 18  
 Tel: +33 1 44 85 44 86  
 Fax: +33 1 46 27 95 59  
 export@chauvin-arnoux.fr  
 www.chauvin-arnoux.fr

**UNITED KINGDOM**  
**Chauvin Arnoux Ltd**  
 Unit 1 Nelson Ct, Flagship Sq, Shaw Cross Business Pk  
 Dewsbury, West Yorkshire - WF12 7TH  
 Tel: +44 1924 460 494  
 Fax: +44 1924 455 328  
 info@chauvin-arnoux.co.uk  
 www.chauvin-arnoux.co.uk

**Middle East**  
**Chauvin Arnoux Middle East**  
 P.O. BOX 60-154  
 1241 2020 JAL EL DIB - LEBANON  
 Tel: +961 1 890 425  
 Fax: +961 1 890 424  
 camie@chauvin-arnoux.com  
 www.chauvin-arnoux.com

 **CHAUVIN  
ARNOUX**  
GROUP