05-090 Raszyn-Rybie, ul. 19 Kwietnia 58 Poland www.czaki.pl tel. +48 22 7202302 fax +48 22 7202305 e-mail czaki@czaki.pl



## **TEMPERATURE SENSOR**

## **type 105**



## **SPECIFICATION**

Application all purpose temperature sensor with interchangeable measuring inserts

Temperature range  $-40^{\circ}\text{C} \dots +1000^{\circ}\text{C}$ Sheathed thermocouple NiCr-NiAl  $(\textbf{K})^{(1)}$ 

Measuring junction insulated<sup>(2)</sup> (grounded on demand)

Class of processing element 1 Sheath material Inconel Length of compensation cable  $L_{\kappa}$  spiral 1,5 m<sup>(2)</sup> Handle and cable operating temperature  $-20^{\circ}\text{C...} + 80^{\circ}\text{C}$ 

Additional accessories plug type MT-K (for use with hand held thermometers)<sup>(2)</sup>

## ORDERING CODE T P 1 0 5 Outer diameter Ø = 1,5, 2 or 3 mm<sup>(2)</sup> Sensor length L = 100 ... 1000 mm<sup>(2)</sup> Additional accessories plug type MT-K

Example for order: TP-105-2-300-MT-K temperature sensor with interchangeable sheathed thermocouple NiCr-NiAl (K) of

outer diameter  $\emptyset = 2$  mm, length L = 300 mm; compensating cable with plug type MT-K.

Additional interchangeable thermocouples please order according to example:

Interchangeable insert: TP-233K-b-800 means interchangeable sheathed thermocouple NiCr-NiAl (K) of

outer diameter  $\emptyset = 1.5$  mm and length L = 800 mm.

Attention: Temperature sensors NiCr-NiAl (K) type 231, 232, 233, 234 also can be used.

<sup>(1)</sup> Other thermocouples on demand

<sup>&</sup>lt;sup>(2)</sup> Other parameters according to customer requirements