






SASK 51.4

Protection plug-in current transformer

Secondary current		5A		1A	
Primary current A	Burden VA	Protection class		Protection class	
		5P5	10P5	5P5	10P5
		Art.-no.	Art.-no.	Art.-no.	Art.-no.
150	1			S34-1616B	S34-1617B
200	1	S34-1706B	S34-1707B	S34-1716B	S34-1717B
	1.5		S34-1707C	S34-1716C	S34-1717C
250	1.5	S34-1806C	S34-1807C	S34-1816C	S34-1817C
	2.5				S34-1817D
300	1.5	S34-1906C	S34-1907C	S34-1916C	S34-1917C
	2.5			S34-1916D	S34-1917D
400	1.5	S34-2006C	S34-2007C	S34-2016C	S34-2017C
	2.5		S34-2007D	S34-2016D	S34-2017D
500	1.5	S34-2106C	S34-2107C	S34-2116C	S34-2117C
	2.5		S34-2107D	S34-2116D	S34-2117D
600	1.5	S34-2206C	S34-2207C	S34-2216C	S34-2217C
	2.5		S34-2207D	S34-2216D	S34-2217D
750	1.5	S34-2306C	S34-2307C	S34-2316C	S34-2317C
	2.5	S34-2306D	S34-2307D	S34-2316D	S34-2317D
	5				S34-2317F
1000	1.5	S34-2506C	S34-2507C	S34-2516C	S34-2517C
	2.5	S34-2506D	S34-2507D	S34-2516D	S34-2517D
	5			S34-2516F	S34-2517F



Primary conductor	50 x 12 mm 2 x 40 x 10 mm
Round conductor	Ø 44 mm
Transformer width	86 mm
Snap-on mounting	—
Sealed shutter	Art.-no. 59042 see page 205
Current transformer for industrial applications	see page 65
Current transformer for tariff applications	see page 178