

HD2305.0



HD2305.0 PORTABLE pH METER

The **HD2305.0** is a portable instrument with a large LCD display. It measures the pH and the redox potential (ORP) in mV. It measures the temperature by using Pt100 or Pt1000 immersion, penetration, contact or air probes. The electrode calibration can be carried out on one, two or three points at 4.01pH, 6.86pH and 9.18pH. The temperature probes are equipped with the automatic recognition SICRAM module which contains the factory calibration data stored inside.

The *Max*, *Min* and *Avg* function calculate the maximum, minimum or average values. Other functions include: the relative measurement REL, the Auto-HOLD function, and the automatic turning off that can also be excluded.

The instruments have IP67 protection degree.

INSTRUMENT TECHNICAL CHARACTERISTICS

Measured quantities: pH, mV, °C, °F

Instrument

Dimensions (Length x Width x Height)	140x88x38mm
Weight	160g (complete with batteries)
Materials	ABS
Display	2x4½ digits plus symbols Visible area: 52x42mm

Working conditions

Operating temperature	-5...50°C
Storage temperature	-25...65°C
Working relative humidity	0...90%RH without condensation

Protection degree IP67

Power

Batteries	3 1.5V type AA batteries
Autonomy	200 hours with 1800mAh alkaline batteries
Power absorbed with instrument off	<20µA

Connections

Input module for temperature probes	8-pole male DIN45326 connector
pH/mV input	Female BNC

Measurement of pH by Instrument

Measurement range	-2.00...+19.99pH
Resolution	0.01
Accuracy	±0.01pH±1 digit
Input impedance	>10 ¹² Ω
Calibration error @25°C	lOffsetl >20mV Slope < 50mV/pH or Slope > 63mV/pH Sensitivity < 85% or Sensitivity > 106.5%
Temperature compensation automatic/manual	-50...+150°C

Measurement of mV by Instrument

Measurement range	-1999.9...+1999.9mV
Resolution	0.1mV
Accuracy	±0.1mV±1 digit
Drift after 1 year	0.5mV/year

Measurement of temperature by Instrument

Pt100 measurement range	-200...+650°C
Pt1000 measurement range	-200...+650°C
Resolution	0.1°C
Accuracy	±0.1°C±1 digit
Drift after 1 year	0.1°C/year

Temperature probes Pt100 sensor using SICRAM module

Model	Type	Application field	Accuracy
TP472I	Immersion	-196°C...+500°C	±0.25°C (-196°C...+300°C) ±0.5°C (+300°C...+500°C)
TP472I.0 1/3 DIN Thin Film	Immersion	-50°C...+300°C	±0.25°C (-50°C...+300°C)
TP473P.I	Penetration	-50°C...+400°C	±0.25°C (-50°C...+300°C) ±0.5°C (+300°C...+400°C)
TP473P.0 1/3 DIN Thin Film	Penetration	-50°C...+300°C	±0.25°C (-50°C...+300°C)
TP474C.I	Contact	-50°C...+400°C	±0.3°C (-50°C...+300°C) ±0.5°C (+300°C...+400°C)
TP474C.0 1/3 DIN Thin Film	Contact	-50°C...+300°C	±0.3°C (-50°C...+300°C)
TP475A.0 1/3 DIN Thin Film	Air	-50°C...+250°C	±0.3°C (-50°C...+250°C)
TP472I.5	Penetration	-50°C...+400°C	±0.3°C (-50°C...+300°C) ±0.6°C (+300°C...+400°C)
TP472I.10	Penetration	-50°C...+400°C	±0.30°C (-50°C...+300°C) ±0.6°C (+300°C...+400°C)
TP49A.0 Class A Thin Film	Immersion	-70°C...+250°C	±0.3°C (-70°C...-50°C) ±0.25°C (-50°C...+250°C)
TP49AC.0 Class A Thin Film	Contact	-70°C...+250°C	±0.3°C (-70°C...-50°C) ±0.25°C (-50°C...+250°C)
TP49AP.0 Class A Thin Film	Penetration	-70°C...+250°C	±0.3°C (-70°C...-50°C) ±0.25°C (-50°C...+250°C)
TP875.I	Globe-thermometer Ø150mm	-30°C...+120°C	±0.25°C
TP876.I	Globe-thermometer Ø50mm	-30°C...+120°C	±0.25°C
TP87.0 1/3 DIN Thin Film	Immersion	-50°C...+200°C	±0.25°C
TP878.0 1/3 DIN Thin Film TP878.1.0 1/3 DIN Thin Film	Photovoltaic	+4°C...+85°C	±0.25°C
TP879.0 1/3 DIN Thin Film	Compost	-20°C...+120°C	±0.25°C

Common characteristics

Temperature drift @ 20°C	0.003%/°C
--------------------------	-----------

4 wires Pt100 and 2 wires Pt1000 Probes

Model	Type	Application field	Accuracy
TP47.100.0 1/3 DIN Thin Film	4 wires Pt100	-50...+250°C	1/3 DIN
TP47.1000.0 1/3 DIN Thin Film	2 wires Pt1000	-50...+250°C	1/3 DIN
TP87.100.0 1/3 DIN Thin Film	4 wires Pt100	-50...+200°C	1/3 DIN
TP87.1000.0 1/3 DIN Thin Film	2 wires Pt1000	-50...+200°C	1/3 DIN

Common features

Temperature drift @20°C

Pt100	0.003%/°C
Pt1000	0.005%/°C

ORDERING CODES

HD2305.0: The kit is supplied with: instrument HD2305.0, 3 1.5V alkaline batteries, operating manual, case.

Electrodes, calibration solutions and temperature probes have to ordered separately.

HD22.2: Laboratory electrode holder composed of base plate with built-in magnetic stirrer, shaft and replaceable electrode holder. Suitable diameter 12mm. Powered by power supplier SWD10 (optional).

HD22.3: Laboratory electrode holder composed of base plate. Flexible arm for free positioning. Suitable for electrodes with diameter 12mm.

pH Electrodes

KP 20: Gel pH filled combined electrode for general use, with S7 screw connector, EPOXY body.

KP 30: Gel pH combined electrode for general use, 1m cable with BNC, EPOXY body.

KP 50: Gel pH combined electrode, porous Teflon ring junction, suitable for emulsions, demineralised water, waste water with S7 screw connector, glass body.

KP 61: 3 diaphragm liquid filled pH combined electrode for wine, milk, cream, etc., S7 screw connector, liquid reference filling, glass body.

KP 62: 1 diaphragm gel pH combined electrode for general use, pure water, varnishes, gel filled, S7 screw connector, glass body.

KP 63: liquid filled pH combined electrode for general use, varnishes, 1m cable with BNC, glass body.

KP 64: Liquid filled pH combined electrode, Teflon ring diaphragm, for wine, varnishes, emulsions, S7 screw connector, glass body.

KP 70: Pointed gel combined pH microelectrode diam. 6 x L=70 mm., with S7 screw connector, EPOXY body, glass tip, open junction for meat and cheese.

KP 80: Pointed gel pH combined electrode, with S7 screw connector, glass body, for cream, milk, viscous material, open junction.

KP100: Flat membrane gel combined pH electrode with S7 screw connector, glass body, for skin, leather, paper.

Characteristics and dimensions of the probes at page WA-76

CP: 1.5m extension cable with BNC/S7 connector for electrode without cable, thread S7.

CP5: 5m extension cable with BNC/S7 connector for electrode without cable, thread S7.

CP10: 10m extension cable with BNC/S7 connector for electrode without cable, thread S7.

CP15: 15m extension cable with BNC/S7 connector for electrode without cable, thread S7.

CE: S7 screw connector for pH electrode.

BNC: female BNC for extension cable

ORP Electrodes

KP 90: REDOX PLATINUM liquid filled electrode with S7 screw connector, glass body.

KP 91: Gel REDOX PLATINUM electrode, 1m cable with BNC, EPOXY body for general purpose light duty.

Characteristics and dimensions of the probes at page WA-76

pH Buffer solutions

HD8642: Buffer solution 4.01pH - 200cc.

HD8672: Buffer solution 6.86pH - 200cc.

HD8692: Buffer solution 9.18pH - 200cc.

Redox Buffer solutions

HDR220: Redox buffer solution 220mV 0.5 l.

HDR468: Redox buffer solution 468mV 0.5 l.

Electrolyte solutions

KCL3M Ready to use solution for electrode refilling – 100 cc



HD22.3



HD8642

HD8672

HD8692

Cleaning and maintenance

- HD62PT:** Diaphragm cleaning (tiourea in HCl) - 500ml.
- HD62PP:** Protein cleaning (pepsin in HCl) - 500ml.
- HD62RF:** Regeneration (fluorhydric acid) - 100ml.
- HD62SC:** Solution for electrode preservation - 200ml.

Temperature probes complete with SICRAM module

- TP472I:** Wire wound Pt100 sensor, immersion probe. Stem \varnothing 3 mm, length 300 mm. Cable length 2 m.
- TP472I.0:** Thin film Pt100 sensor, immersion probe. Stem \varnothing 3 mm, length 230 mm. Cable length 2 m.
- TP473PI:** Wire wound Pt100 sensor, penetration probe. Stem \varnothing 4mm, length 150 mm. Cable length 2 m.
- TP473PO:** Thin film Pt100 sensor, penetration probe. Stem \varnothing 4mm, length 150 mm. Cable length 2 m.
- TP474C.I:** Wire wound Pt100 sensor, contact probe. Stem \varnothing 4mm, length 230mm, contact surface \varnothing 5mm. Cable length 2 m.
- TP474C.O:** Thin film Pt100 sensor, contact probe. Stem \varnothing 4mm, length 230mm, contact surface \varnothing 5mm. Cable length 2 m.
- TP475A.O:** Thin film Pt100 sensor, air probe. Stem \varnothing 4mm, length 230mm. Cable length 2 m.
- TP472I.5:** Thin film Pt100 sensor, penetration probe. Stem \varnothing 6mm, length 500 mm. Cable length 2 m.
- TP472I.10:** Thin film Pt100 sensor, penetration probe. Stem \varnothing 6mm, length 1000mm. Cable length 2 m.
- TP49A.O:** Thin film Pt100 sensor, immersion probe. Stem \varnothing 2,7mm, length 150mm. Cable length 2 m. Aluminium handle
- TP49AC.O:** Thin film Pt100 sensor, contact probe. Stem \varnothing 4 mm, length 150mm. Cable length 2 m. Aluminium handle
- TP49AP.O:** Thin film Pt100 sensor, penetration probe. Stem \varnothing 2,7mm, length 150mm. Cable length 2 m. Aluminium handle
- TP875.I:** Wire wound Pt100 sensor, 150mm diameter globe-thermometer equipped with handle and SICRAM module. Cable length 2 m.

- TP876.I:** Wire wound Pt100 sensor, 50mm diameter globe-thermometer equipped with handle and SICRAM module. Cable length 2 m.
- TP87.O:** Thin film Pt100 sensor, immersion probe. Stem \varnothing 3 mm, length 70 mm. Cable length 2 m.
- TP878.O:** Thin film Pt100 sensor, contact probe for solar panels. Cable length 2 m.
- TP878.1.O:** Thin film Pt100 sensor, contact probe for solar panels. Cable length 5 m.
- TP879.O:** Thin film Pt100 sensor, penetration probe for compost. Stem \varnothing 8 mm, length 1000 mm. Cable length 2 m.

Temperature probes without SICRAM module

- TP47.100.0:** Thin film Pt100 sensor, immersion probe. Stem \varnothing 3mm, length 230mm. Connection cable 4 wires with connector, length 2 m.
- TP47.1000.0:** Thin film Pt1000 sensor, immersion probe. Probe's stem \varnothing 3mm, length 230mm. Connection cable 4 wires with connector, length 2 m.
- TP47:** Connector for Pt100 4-wire and Pt1000 2-wire probes without SICRAM module.
- TP87.100.0:** Thin film Pt100 sensor, immersion probe. Stem \varnothing 3mm, length 70mm. 4-wires connection cable with connector, length 1 m.
- TP87.1000.0:** Thin film Pt1000 sensor, immersion probe. Stem \varnothing 3mm, length 70mm. 2-wires connection cable with connector, length 1 m.

